



REQUEST FOR QUOTATION
Solicitation No. RSU-62-19
Quotation No. 19-11-159

Date : November 21, 2019
Company Name: _____
Address : _____

Sir/Madame:

Please quote your lowest price on the Item/s below, subject to the General Conditions and Eligibility Requirements for the Suppliers, stating the shortest time of the delivery and submit your quotation duly signed by your representative not later than **November 25, 2019** at exactly 5:00 in the afternoon in the return envelope attached herewith.

Project: Procurement of Scientific Equipment for the College of Engineering and Technology
Total ABC: PhP1,331,020.84
QTY: 22

LOT-4: ELECTRICAL ENGINEERING LABORATORY EQUIPMENT (ABC: PhP953,750.00, QTY: 20)


UNIT	ITEM DESCRIPTION	QTY	ESTIMATED UNIT COST	ESTIMATED COST
unit	3-Phase Power Analyzer Analyzer; 600Vrms, 30Arms/1Arms Internal Shunts; 20Vpk (2mm Banana Plug); 45-850Hz Range; 5-2000V Range; 30A Shunt (1-200A) & 1A Shunt (12.5mA - 5A); 1ph (2-3W), 3ph (3W,4W,3W - 3V3A); USB Host, USB, Ethernet, RS232, GPIB; Power Input - 100Vto240V, 60Hz, 120VA Max.; 5.2"x15.5"x13.2" Dimension	1		
unit	Complete Set PLC Training Equipment (8 Digital I/O; 8 Analog I/O; Temp.Sensor; Humidity Sensor; Floatless Relay; HMI-10" touchscreen Panel; 8 Momentary Button; 8-24V- Pilot Light; 8-24V Dry Contact Relay; 1-PC Set with Software Embedded)	1		
unit	5kV DC Max. Insulation Resistance Tester (Megger) Dimension: 9.1x9.1x9.1 Inches; 2-in-1 insulation Multimeter w/Clamp	1		
unit	Earth Tester 0-20 Ohm Range (0.10 ohm resolution); 0-200ohm range (0.1ohm resolution); 0-2000ohms range (1ohm resolution); + or - 2% reading + 2 Digits or + or - 0.1ohm; 0-200VAC, 40-500Hz; 80% Operating Humidity; 32-104 deg.F., Operating Temperature	1		
unit	Complete Set Electrician Tools (Pliers; Diagonal Side Cutting; Needle Nose Pliers; Strippers; Channel Locks; 6 Models Screwdrivers; Knives&Pocket Knives; Pipe Reamer; Electrician Level; Voltage Detector; Tape Measure; Roto Split; Rock Saw; Multitester; Step Drill Bits; Safety Googles; Cut Resistive Gloves; Blade Cutter)	5		
unit	1-Phase, 230V Automatic Transfer Switch (ATS)	5		
unit	3-Phase, 230V/18V Transformer	5		
unit	Thermal Scanner (8-14 micron spectral wavelengths; 100,000 imaging pixels and up; Facilitate extreme temperature in excess 2000 deg. F.; imaging sensor refresh rate no less than 46 times per second; rechargeable batteries lasts for 5 hrs & up; Video/images is downloadable to a PC using USB; 2.4 GHz Wireless Transmitter)	1		
TOTAL		QTY	20	ESTIMATED COST



LOT-6: AGRICULTURAL ENGINEERING LABORATORY EQUIPMENT (ABC: PhP377,270.84, QTY: 2)

UNIT	ITEM DESCRIPTION	QTY	ESTIMATED UNIT COST	ESTIMATED COST
unit	OVEN NATURAL CONVECTION, STANDARD 50 Liters ThermoStable™ ON Ovens, Gravity Convection-type, 50 liters With 2×Wire Shelves, Digital Fuzzy Control, Jog-Dial with Push Button, Digital LCD with Backlight, up to 230°C, ±0.5°C with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System ■ Digital Fuzzy Control System Implementing Superior Temperature Accuracy ■ Optimized Air Flow by Gravity Convection Mechanism ■ Patented Jog-Dial Control System ■ UL / CUL Certified ■ CE Certified ■ GD(Good Design)-mark ■ PL(Product Liability) Insurance; Interior Dimension:370x350x420mm; Exterior Dimension: 518x647x724mm; Heater Power 650W;Temp Range:+5degC to 230degC; Control resolution: +/- 0.1 degC; RS 232 port; Heat up time 30min to 100degC; Display: digital LCD with backlight; External material: powder coated steel; Internal material: stainless steel 304; Insulation: wool; Safety device: Over temperature and over current protector, sensor error detector; Net wt: 44kg; Power consumption: 674 W; Power supply: 1phase, 230V, 6Hz. With desiccators 3 units (6", 8" and 12") borosilicate glass with cover and porcelain plate and 1kg desiccant	1		
unit	Halogen Moisture Analyzer A&D, Japan Model: MX-50 Capacity: 51g Min. Display-Moisture Content 0.01%/0.1% Min. Display-Weight 0.001 g Temp: 50-200°C With SRA (Secondary Radiation Assist) filter. With SHS (Super Hybrid Sensor). High moisture content measurement at 0.001% resolution. Standard WinCT-Moisture software (for MS&MX) for real-time graph displaying. With Sodium Tartrate Dihydrate standard for accuracy checking. Laptop for data gathering included; i7 processor.	1		
TOTAL		QTY	2	ESTIMATED COST

Yours,


MARIO A. FETALVER JR., Ph. D.
 BAC Chairperson

Canvassed by:

LARRY I. FIRMALO
 Procurement Officer

BIDS & AWARDS COMMITTEE (BAC)
ROMBLON STATE UNIVERSITY
Odiongan, Romblon

Sir/Madame:

Delivery Period : _____



Warranty : _____
Price Validity : _____

After having carefully read accepted your General Conditions, I/We quote you on the item at prices noted above.

Printed Name / Signature

Tel. No. /Cellphone No. _____

Email Address _____

Date: _____

REQUEST FOR QUOTATION

Terms & Conditions:

1. All entries must be type/hand-written.
2. Delivery period within 15 calendar days.
3. Warranty shall be for a period of six (6) months for supplies and materials, one (1) year for equipment, from the date of acceptance by the procuring entity.
4. Price validity shall be for a period of three months.
5. PhilGEPS registration Certificate shall be attached upon submission of the quotation.
6. Bidder shall submit original brochures showing certifications of the production being offered.
7. Payment shall be made after the inspection.
8. Deliver items at Supply Office, Romblon State University, Odiongan, Romblon (042-567-5375)

CHECKLIST OF ELIGIBILITY REQUIREMENTS FOR THE BIDDERS/SUPPLIERS:

The Eligibility Envelope shall contain the following:

1. Mayor's/Business permit
2. PhilGEPS Registration Number
3. Income/Business Tax Return
4. Omnibus Sworn Statement

Note: Submitted documents must be properly authenticated.