



Republic of the Philippines
ROMBLON STATE UNIVERSITY
Odiongan, Romblon
Tel No. (042) 567-5273
Email: romblonstateu@gmail.com
URL: rsu.edu.ph

BIDS AND AWARDS COMMITTEE

ABSTRACT OF QUOTATION
Solicitation No. **RSU-2021-07-062**
ABC: **PhP835,871.00**
QTY:**4616**

Procurement of Various Electrical and Construction Supplies for the Different Units and Offices of Romblon State University

UNIT	ITEM DESCRIPTION	QTY	ESTIMATED UNIT COST	ESTIMATED COST
bags	cement	45		
bags	portland cement	250		
bags	tile adhesive	60		
box	5.5mm ² THHN Wire, 450 meters, Thermoplastic High Heat Resistant with Nylon Conductor: Made from pure annealed virgin copper with 100% conductivity, PVC Insulation: Flame Retardant PVC, Moisture, Oil and Gasoline Resistant, Meets or Exceeds PNS 35 standard and Philippine Electrical Requirements	3		
cu.m.	fine sand (washed/screened)	33		
cu.m.	gravel	11		
cu.m.	sand	5		
kgs	#16 G.I. Tying wire	15		
kgs	tile grout	60		
m	wire mesh screen (pang-ayag)	3		
pc	angle grinder	1		
pc	Hacksaw frame/handle	1		
pc	Panel Box on 18 branches, bolt type	1		
pc	retardant, general purpose 7-mil (0.177 mm) thick polyvinyl chloride (PVC) based tape	40		
pcs	10mmØ RSB	120		
pcs	concrete cutting disk 4"	4		
pcs	glazed tiles 40cmx40cm (marbling white)	3900		
pcs	Hacksaw blade	6		
pcs	rubber mallet	2		
unit	3dia Circuit Breaker, Bolt-on 150 Amperes	1		
unit	50 mm ² THHN Wire, at least 90 meters	1		

Serving with Honor and Excellence!



Republic of the Philippines
ROMBLON STATE UNIVERSITY
 Odiongan, Romblon
 Tel No. (042) 567-5273
 Email: romblonstateu@gmail.com
 URL: rsu.edu.ph

BIDS AND AWARDS COMMITTEE

unit	Circuit Breaker 40A, 230/400 VAC Ue, 2-pole. 6KA Interrupting Capacity, C tripping Curve, Compliant to IEC/EN 60898-1, 100% designed and manufactured by Schneider Electric, Electrical Life 4,000 Cycle Mechanical Life 10,000 Cycles, DIN-rail mount method of installation	18		
unit	Safety Breaker Bolt On 2 Pole - 30A <ul style="list-style-type: none"> • Breaker Type: Bolt On • Bureau of product standards approved • Poles: 2 • Voltage: 220V 	18		
unit	Utility Box 20mm x1/2; Fire Retardant, Shock resistant, Can withstand high impact	18		
TOTAL	QTY	4616	ESTIMATED COST	